FM2-CTH

Flush mount CO₂, Temperature and Humidity Sensor



Description

Stylish flush mount Sensor with slotted vents for airflow across the sensors, single gang flush mounted plate and only 12mm deep. CO₂ ,Temperature and Humidity sensors 3 off 0 -10 outputs. Available in a wide range of materials and finishes

Material

Brushed stainless steel, Polished stainless steel, Lacquered Brass, Powder coated in RAL colours. Any plated finish to match existing electrical hardware (See our leaflet for the range of finishes).

Specification

Plate: 86 x 86mm x 12mm deep. Metal plate

with choice of black or white slotted grid fits standard single gang back box

(minimum 35mm deep)

Power supply: 24Vac/dc

CO2 sensor: Non dispersive Infra-red technology.

Self calibrating ABC algorithm which monitors and adjusts the calibration (for non continuous occupation applications)

Range: 0 - 2000ppm Output: 0 - 10Vdc

Temperature Range: 0 - 40 degC Sensor Output: 0 - 10Vdc


Humidity Sensor Range 0 - 100% (3% accuracy)

Output: 0 - 10Vdc

LED indication Red / Yellow/ Green LEDs to indicate CO2

(optional) level

Green < 800ppm Yellow 800 - 1000ppm Red > 1000ppm




Associated Products

BACnet CO₂ sensors CO₂ / Temp / Humidity sensors Surface mount CO₂ sensors CO₂ level Indicators









If this product doesn't quite suit your application - Contact us to discuss a bespoke version